



Gold Label Technology Limited

高力堡科技有限公司

Gainscha

Focus On High-end Quality

Build Your Ideal Printer

Multifunction, Super quality, Fashion

😊 Satisfy 💎 High-quality ❤️ Heartfelt



GP-1825T/GP-1835T

Thermal Transfer Barcode Printer



GP-1825TP/GP-1835TP

Available peeler module



GP-1825TC/GP-1835TC

Available cutter module



Optional external paper holder



Peeler

Peeler added, achieve label peeling rapidly



Cutter

Cutter added, convenient for users to cut off label



Media width

120mm media outlet support wider media width



Four interfaces

USB/Serial/Parallel/Ethernet interfaces, meet different requirements

Unit 13, 6/F, Block B, Hoi Luen Industrial Centre, 55 Hoi Yuen Rd., Kwun Tong, KLN, HK

香港九龍官塘開源道55號開聯工業中心B座6樓613室

Tel : (852)23053988 Fax : (852) 3694 0599 email: sales@goldlabeltech.com <http://www.goldlabeltech.com>



Gainscha



GP-1825T/GP-1835T
Applications and industries

Amusement park, Cinema
Exhibition, lottery tickets
Shopping mall
Food takeaway



Ticket Industry

Hospital bills
Prescriptions
Check receipt
Medication guide
Test tube label
Wristband label



Medical Industry

Washing mark
Jewelry label, Fixed
assets label
Machinery room
Identification



Clothing & Jewelry & Electricity Industry

Outbound warehousing
Shipping label
Sample label
E-commerce label
Distribution label
Logistics label



Logistics & Warehousing Industry

Specifications

Model	GP-1825T	GP-1835T
Print Method	Thermal Transfer / Direct Thermal	
Print Command	TSPL	
Print Resolution	203DPI	300DPI
Print Speed	2~6inch/s(152mm/s)	2~5inch/s(127mm/s)
Max. Print Width	104mm	106mm
Memory	SDRAM: 8MB, FLASH: 4MB	
Interface	USB+Serial+Parallel+Ethernet (standard)	
Graphics	Monochrome PCX, BMP and other image files can be downloaded to FLASH/DRAM	
Barcode	CODE128, EAN128, ITF, CODE39, EAN13, EAN13+2, EAN13+5, EAN8, EAN8+2, EAN8+5, CODABAR, POSTNET, UPC-A, UPC-A+2, UPC-A+5, UPC-E, UPC-E+2, UPC-E+5, CPOST, MSI, MSIC, PLESSEY, ITF14, EAN14, QRCODE	
Character Set	Common single-byte fonts: FONT 0 to FONT 8	
Character Enlargement/Rotation	1 ~10 times enlargement in horizontal and vertical directions; 0°, 90°, 180°, 270°degree rotation	
Media Type	Continuous, die-cut, fan-fold, black mark	
Media Width	Max.120mm (4.72") Min.20mm (0.78") (include backing paper)	
Media Roll OD	127mm (5")	
Media Thickness	Max. 0.254mm (10mil) Min. 0.06mm (2.36mil)	
Media Roll Core Size	Φ25.4mm~38mm (1"~1.5")	
Ribbon OD	Max.67mm	
Ribbon Length	Max.300m	
Media Roll Core Size	1 inch(25.4mm)	
Ribbon Width	Max.110mm, Min.30mm	
Ribbon Rolling Up Method	Outward Rolling	
Paper Off Mode	Tear off (standard), Cut off, Peel off (optional)	
Cutter Service Life	1 million times	
Paper Output Method	Front paper output	
Power Supply	DC24V/2.5A	
Operation Environment	5~45°C, 20~90%RH	
Storage Environment	-25~55°C, 20%~93%RH	
Printer Weight	2.5KG	
Printer Dimensions	278×210×180mm	
Packaging Dimensions	370×260×235mm	
Print Head Reliability	30KM	

Unit 13, 6/F, Block B, Hoi Luen Industrial Centre, 55 Hoi Yuen Rd., Kwun Tong, KLN, HK
香港九龍官塘開源道55號開聯工業中心B座6樓613室

Tel : (852)23053988 Fax : (852) 3694 0599 email: sales@goldlabeltech.com <http://www.goldlabeltech.com>